

# PROFI 232

"PROFI232" EXTERNAL PROFIBUS INTERFACE IN CASE FOR DIN BAR,  
FOR "ENTERPRISE" SERIES INDICATORS



External interface which allows to connect the CPWE and 3590E weight indicators to the Profibus networks. Wide range of available data.

**The best solution  
for advanced industrial  
applications**

## FUNCTIONING

- Complete functionality from the Profibus-DP Slave, in according to IEC 61158
- 16 input bytes / 16 bytes output on SSC interface
- Automatic baud rate selection: from 9600 bit/s to 12Mbit/s
- Wide range of available data depending on the weight indicator to which it is applied
- Available for CPWE and 3590E indicators, in the versions with management of the Profibus protocol

## TECHNICAL FEATURES

- ABS case for panel mounting on DIN bar
- Dimensions l x w x h (mm): 53 x 58 x 90
- Power supply: from 12 to 24Vdc
- RS232 and RS485 serial ports on terminal board
- Profibus port on 9 Pin connector
- Board optoisolation against electric or electrostatic discharges

**COVENTRY SCALE COMPANY**



COVENTRY SCALE COMPANY LTD

BARKERS BUTTS LANE 137 - CV61EB - COVENTRY - UNITED KINGDOM

Tel. 0044-2476-593500

Fax. 044-2476-601239

E-mail [info@coventryscale.co.uk](mailto:info@coventryscale.co.uk)

Web [www.coventryscale.co.uk](http://www.coventryscale.co.uk)