

MAIN FEATURES

- 5-key functional waterproof keypad.
- Backlit 25mm LCD display with 6 high contrast digits with icons for showing the active functions.
- Easy to clean ABS IP68 case, resistant to harsh and corrosive environments.
- Suitable for use on the table, column, or wall.
- Fitted with fixing bracket with adjustable inclination.
- A/D 24 bit, 4 channel converter, max. 200 conv./sec. autoselect, and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 μ V/d in CE-M approved versions for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Power supply through built-in rechargeable battery, with 60h operating time, and fitted with external 12Vdc battery charger.

MAIN CERTIFICATIONS

- EC Type Approval (EN45501)
- OIML R76

FUNCTIONS

- MAIN FUNCTIONS:
 - Zeroing
 - Automatic tare
 - Presettable tare
 - Printing in 1, 2 or 3 copies
 - Data transmission to PC.
- OPERATING MODES:
 - High Resolution Weighing x 10
 - Net/Gross or lb/kg conversion
 - Accumulation
 - Formula weighing
 - +/- Checkweighing
 - Percentage weighing
 - Approved transmission of the weight to PC/PLC or data recording on MMC/USB (with Alibi memory ALMEM option)
 - Counting
 - In/Out Truck weighing
 - Hold and Peak.

I/O SECTION

- RS232/C bidirectional port on RJ11 connector for quick connection (optional RS485) on screw terminal, configurable for PC, PLC, or additional remote display.
- RS232/C bidirectional port configurable for connection to printer or labeller.

